05.09.2016
12.04.2017
1.01-EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier:

Substance name: Mineral Bond LV, Component A

Index number: Not applicable (mixture)

Synonyms: Not applicable

CAS number: Not applicable (mixture)

EC number: Not applicable (mixture)

Registration number: excluded from registration (polymer).

1.2. Relevant identified uses of the substance or mixture and uses advised against <u>Relevant identified uses:</u>

Component A of 2-component, high strength silicate resin. It is suitable for grout stabilization, for heavily cracked rock mass, gas sealing and water stopping.

Uses advised against:

Any other uses than those listed should be consulted with the Supplier.

1.3. Details of the supplier of the safety data sheet

Supplier:

Rocbolt Technologies (Pty) Ltd 42 Steel Rd., Spartan P.O. Box 15, Isando, 1600 Telephone: (011) 970 – 1643 Fax: (011) 970 – 3596

1.4. Emergency telephone number

Telephone: (011) 970 - 1643 Fax: (011) 970 - 3596

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture <u>Classification according to Regulation (EC) No 1272/2008 (CLP)</u>
Skin Irrit. 2; H315
Eye Irrit. 2; H319
<u>Additional information:</u>
For full text of Hazard- and EU Hazard-statements: see SECTION 16

2.2: Label elements Labelling according to Regulation (EC) No 1272/2008 [CLP] <u>Hazard pictograms</u>



Signal word: Warning

Hazard statements:

H315 - Causes skin irritation. H319 - Causes serious eye irritation.

Precautionary statements:

P262 - Do not get in eyes, on skin, or on clothing

P280 - Wear protective gloves/protective clothing/ eyes/face protection

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



SECTION 3: Composition/information on ingredients

3.1. Substances Not applicable

3.2. Mixtures

Name Registration number	% [weight]	CAS No	EC No	Classification according to Regulation (EC) No 1278/2008 (CLP)
silicic acid , sodium salt 01-2119448725-31-XXXX	80 - 100	1344-09-8	215-687-4	Skin Irrit. 2; H315 Eye Irrit. 2; H319

Additional information: For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the event of accident or ailments appearing caused by the product it is necessary to protect the injured against continued exposure and immediately provide medical attention to him.

Poisoning by inhalation

Move to fresh air.

Skin contamination

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contamination

Rinse immediately with plenty of running water (for 15 minutes), seek medical attention from a specialist.

Poisoning by swallowing Rinse the mouth. Drink 1-2 glasses of water.

4.2. Most important symptoms and effects, both acute and delayed Alkaline solution. Impact on the unprotected eyes can damage the eyes. Prolonged or repeated impact on the risk of unprotected skin may cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed Each time, if you use a doctor recommended to provide the assisting these SDS.

SECTION 5: Firefighting measures

5.1. Extinguishing media: Suitable extinguishing media: Non-combustible Unsuitable extinguishing media: Non-combustible

5.2. Special hazards arising from the substance or mixture: Hazardous combustion products: Non-combustible

5.3. Advice for firefighters Avoid direct contact with skin and eyes. Apply general purpose measures for personal protection equipment. The substance is soluble in water. Avoid getting into drains / surface water / ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of accidental spills contaminated site rampart, used sand or sorbent remains mechanically gather, be disposed of. Prevent from entering the municipal water system - sewage, water courses and the soil. Do not rinse with water. Prevent spraying and aerosol inhalation of the substance with air. Avoid contact with skin and eyes, avoid contact with substance, and provide adequate ventilation in enclosed spaces. Apply protective clothing and rubber gloves to protect against dirt, apply a mask or respirator with dust filter A/P2; use face protection-goggles. Remove contaminated clothing and wash before reuse.

+27 11 878 6800 www.rocbolt.com TECHNOLOGIES

6.2. Environmental precautions:

Do not empty into drains / surface water / ground water. Methods for cleaning and take-up: Remove mechanically. In the case of environmental contamination with plenty of substance notify to local authority and emergency services.

6.3. Methods and material for containment and cleaning up

The whole material is released into the environment to collect mechanically. Provide material collected for recycling. Do not rinse with water. Do not neutralize.

6.4. Reference to other sections

Use the control measures and personal protective equipment described in section 8 of this SDS. The released material to follow the rules described in section 13 of this SDS - Waste Disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Store in original containers. Empty containers to the end. Store in a dry place. Avoid contact with skin and eyes. Follow the general principles of occupational health and safety of chemicals, good industrial practice and the manufacturer's recommendations. If there is a need to handling the substance, use personal protective gloves, eye protection, clothing according to the principles described in section 8 of this SDS.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original containers. Store in tightly sealed, closed containers. Do not store near acids. Do not store in containers made of or coated with zinc, aluminium.

7.3. Specific end use(s):

No information on specific end-uses. See also subsection 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

silicic acid , sodium salt

DNEL

Application Area	Exposure routes	Health effect	Value
Workers	Inhalation	Long-term systemic effects	5.61 mg/m ³
Workers	Skin contact	Long-term systemic effects	1.59 mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	1.38 mg/m ³
Consumers	Skin contact	Long-term systemic effects	0.8 mg/kg BW/d
Consumers	Oral	Long-term systemic effects	0.8 mg/kg BW/d

PNEC

Compartment	Value
Marine water	1 mg/l
Fresh water	7,5 mg/l
Marine sediment	no PNEC available
Fresh water sediment	no PNEC available
Sewage treatment plant	348 mg/l
Aquatic intermittent release	7,5 mg/l

1,2-Ethanediol

DNEL

Application Area	Exposure routes	Health effect	Value
Workers	Inhalation	Long-term local effects	35 mg/m ³
Workers	Skin contact	Long-term systemic effects	106 mg/kg BW/d
Consumers	Inhalation	Long-term local effects	7 mg/m ³
Consumers	Skin contact	Long-term systemic effects	53 mg/kg BW/d

PNEC

Compartment	Value
Soil	1,53 mg/kg
Marine water	1 mg/l
Fresh water	10 mg/l
Marine sediment	3,7 mg/kg
Fresh water sediment	37 mg/kg
Sewage treatment plant	199,5 mg/l

+27 11 878 6800 www.rocbolt.com TECHNOLOGIES

Aquatic intermittent release 10 mg/l

8.2. Exposure controls

Avoid contact with eyes, mucous membranes and inhalation of vapours. It is forbidden to smoking, drinking, eating while working.

Observe the typical standards of hygiene at work.

Respiratory protection:

In conditions of insufficient ventilation, while spraying the product, it is recommended to wear a mask with the filter type A2-P2 or better.

Eye protection:



Wear approved chemical safety goggles with side shields where eye exposure is reasonably probable, meet the requirements of EN 166.

Hand protection:

Use suitable protective gloves, such as: polychloroprene $\geq 0,5$ mm thick and breakthrough time \geq 480 minutes; nitril $\geq 0,35$ mm thick and breakthrough time \geq 480 minutes; butyl rubber $\geq 0,5$ mm thick and breakthrough time \geq 480 minutes or fluoro-rubber $\geq 0,4$ mm thick and breakthrough time \geq 480 minutes.
For prolonged or repeated skin contact use suitable protective gloves meet the requirements of EN 374

Skin protection:



According to the exposure when handling the product wear suitable protective clothing, aprons, protective boots.

General recommendations:

See also section 7.

Provide adequate ventilation. Remove contaminated clothing immediately. Wash hands before breaks and after work. Wash contaminated gloves before removing. At work do not eat, drink or smoke. Avoid contact with skin. Do not get in eyes. Do not breathe vapours.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	light brown clear liquid
Odour	Characteristic
Odour threshold	unidentified
рН	11- 13
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	Not applicable.
	Liquid, incombustible.
Evaporation rate	not determined
Flammability (solid, gas)	Liquid, incombustible
Lippor/lower flammability or explosive limite	Not applicable.
Upper/lower flammability or explosive limits	Liquid, incombustible.

TECHNOLOGIES

www.rocbolt.com

+27 11 878 6800

Vapor pressure	not determined
Vapor density	not determined
Relative density	1.45 ± 0.05 g/cm ³
Solubility(ies)	Mixed in water in any ratio
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	Not applicable.
	Liquid, incombustible.
Decomposition temperature	not determined
Viscosity	300 ± 50 mPas

9.2. Other information

No other information.

SECTION 10: Stability and Reactivity

10.1. Reactivity

Alkalinity, water soluble substance.

10.2. Chemical stability

Stable under normal condition storage and handling.

10.3. Possibility of hazardous reactions

Reacts with acids: Heat released.

10.4. Conditions to avoid Avoid heat sources.

10.5. Incompatible materials

Acids; aluminium, zinc, tin, lead.

10.6. Hazardous decomposition products Under normal conditions, the substance is not degradable.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

silicic acid , sodium salt	1,2-Ethanediol
LD50 Oral - Rat = 3400 mg/kg bw	LD50 Oral - Rat - 4.700 mg/kg
LC50 Inhalation - Rat > 2.06 g/m ³ :	LD50 Dermal - Rabbit - 10.626
LD50 Dermal - Rat > 5000 mg/kg bw	mg/kg

Skin corrosion/irritation

silicic acid , sodium salt	1,2-Ethanediol
Skin Irrit.2 H315	Skin – Rabbit Result: No skin irritation

Serious eye damage/eye irritation

1,2-Ethanediol
Eyes – Rabbit
Result: Mild eye irritation - 24 h

Respiratory or skin sensitisation

silicic acid , sodium salt	1,2-Ethanediol
Based on the category approach, sodium silicate is not sensitising.	No data available

Germ cell mutagenicity

Shicky	
silicic acid , sodium salt	1,2-Ethanediol
In vitro: negative, in vivo: negative Not classified	No data available

Carcinogenicity

silicic acid , sodium salt	1,2-Ethanediol
----------------------------	----------------

TECHNOLOGIES

www.rocbolt.com

+27 11 878 6800

ROCBOLT TECHNOLOGIES: MINING

Mineral Bond LV, Component A

No reliable data available. In	This product is or contains a
addition, sodium silicate does not	component that is probably not
carry any structural alerts for	carcinogenic based on its IARC,
carcinogenicity	ACGIH, NTP, or EPA classification.

Reproductive toxicity

ty	
silicic acid , sodium salt	1,2-Ethanediol
Not classified	Laboratory experiments have shown teratogenic effects. Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific target organ toxicity - single exposure

silicic acid , sodium salt	1,2-Ethanediol
Not classified	No data available

Specific target organ toxicity - repeated exposure

silicic acid , sodium salt	1,2-Ethanediol
Not classified	Oral - May cause damage to organs
	through prolonged or repeated
	exposure Kidney

Aspiration hazard

silicic acid , sodium salt	1,2-Ethanediol
Not classified	No data available

SECTION 12: Ecological information

12.1. Toxicity Silicic acid, sodium salt Acute toxicity to fish: LC50 (96 h): 1108 mg/L (Brachydanio rerio) LC50 (96 h): 260 - 310 mg/L (Onchorhynchus mykiss) NOEC (96 h, Mortality): 348 mg/L (Brachydanio rerio) Long-term toxicity for fish: No NOEC available. Acute toxicity for invertebrates: EC50 (48 h): 1700 mg/L (Daphnia magna) Long-term toxicity for algae: EC50 (72 h, biomass): 207 mg/L (Scenedesmus subspicatus) EC50 (72 h, growth rate): > 345.4 mg/L (Scenedesmus subspicatus) Exposure for aquatic environment is not sufficient to classify the substance. Because of the physical properties extremely low vapor pressure - release to the atmosphere during use of the substance is not possible 12.2. Persistence and degradability As inorganic substances and in view of their chemical structure, soluble silicates are not amenable to biodegradation. In water, the substance is hydrolyzed. 12.3. Bioaccumulative potential The substance has a low potential for bioaccumulation, which was confirmed toxicokinetic studies on vertebrates 12.4. Mobility in soil Due to good solubility in water can penetrate into the surface waters of the release site and can be detected at points located far away from this place 12.5. Results of PBT and vPvB assessment Not applicable 12.6. Other adverse effects No other effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

www.rocbolt.com +27 11 878 6800 TECHNOLOGIES

Avoid or minimize waste material production. The material must be disposed in accordance with local or national rules (Waste Act). Unrefined material is not suitable for disposal. Do not let waste material, even in small quantities, down to wastewater, sewage system or watercourses. Emptied packaging must be passed to authorized waste receiver.

SECTION 14: Transport Information

14.1. UN numberNot dangerous goods14.2. UN proper shipping nameNot dangerous goods

14.3. Transport hazard class(es) Not a hazardous material under the provisions of RID and ADR

14.4. Packing group Not dangerous goods

14.5. Environmental hazards

Not a hazardous material for environmental.

14.6. Special precautions for user

Alkaline substance. The Accidental release (spill) to collect the mechanical application of personal protection measures described in section 8 of this SDS.

14.7. Transport bulk according to Annex II of Marpol and the IBC Code

The substance is not transport in bulk.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1. Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) and establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC). No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC as amended, (REACH) (OJ EU L of 2006 No. 396, item 1). 2. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (OJ EU L of 2008 No. 35, item 1).

3. Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No. 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (OJ EU L of 2015 No. 132).

4. Commission Directive No. 2000/39/EC; 2006/15/EC and 2009/161/EC establishing first, second and third lists of indicative occupational exposure limit values (OJ EU L 2000, No. 142, item 47; OJ EU L 2006, No. 38, item 36; OJ EU L of 2009 No. 338, item 87).

15.2 Chemical Safety Assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The full version of the hazard classes and category codes from sections 2 and 3:

- Skin Irrit. 2 Skin corrosion/irritation, category 2.
- Eye Irrit. 2 Serious eye damage/eye irritation; category 2.
- Acute Tox. 4 Acute toxicity (oral); category 4.

STOT RE 2 - Specific target organ toxicity — repeated exposure; category 2

Full text of H-sentences (Hazard statements) referred to under sections 2 and 3:

H302 - Harmful if swallowed.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H373 - May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

DNEL - Derived No Effect Level

PNEC - Predicted No Effect Concentration

The current edition of the safety data sheet replaces the previous edition.



The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

END of the MSDS

